

# XTRA3300He

TECHNICAL SPECIFICATIONS

Print			
Print Head	Epson T3200		
Drop Size	4-12pl		
Resolution	Up to 705×2400dpi		
Productivity			
Printing mode	Express Mode	Production Mode	Quality Mode
Speed	99sqm/hr	68sqm/hr	48sqm/hr
Ink Type	LED UV ink		
Color Scheme	4-10 colors, white and varnish option		
LED UV lamp	LED cold light source with low energy consumption, long working life.		
Cartridge capacity	2.5liter		
Media handing system			
Media loading	Roll to roll industry feeding & take-up device with tension system		
Media thickness	Up to 45mm		
Printing format	Width up to 330cm. Roller diameter up to 35cm		
Data transfer			
Data interface	USB3.0		
RIP Software	Photoprint sever Flora. Onyx.		
Color management	ICC based color, adjustment curves, density adjustment		
File format	Tiff, Jpeg, Jdp, Postscript, PDF, EPS, etc		
Dimensions			
Printer	600cmx 155cm x 160cm		
Package dimension	620cm x 187cm x 206cm		
Printer weight	3000kg		
Environment requirements			
Temperature	20-30°C		
Humidity	40-80% non-condensing		
Power requirements			
Power	209-231V AC. single phase. 50/60Hz. 25A printer 13A UV lamp		
Warranty			
	One-year warranty. Please contact local distributor for accurate data.		



# XTRA3300He


Hi-Speed, Hi-res UV Hybrid Printer



**RTZ** Shenzhen Runtianzhi Digital Equipment Co., Ltd.



ADD: Guanbao Road No.9, Luhua Community, Guanhu Street, Longhua District, Shenzhen, Guangdong, China  
P.C.: 518110  
Tel: +86-755-27521666  
Fax: +86-755-27521866  
Email: sales@floradigital.com.cn



[www.floraprinter.com](http://www.floraprinter.com)

# XTRA3300He

Hi-Speed,Hi-res UV Hybrid Printer

- Standard 4- 10 colors, white and varnish option
- Adjustable LED curing system
- Grayscale printhead, variable ink drop size 4-12pl
- Printing speed up to 99sqm/h
- Resolution up to 705\*2400dpi
- 4-level grayscale printing
- RIP software Photoprint sever Flora. Onyx
- Caldera for option
- 3-layer spot color printing. CWC, WCV modes supported
- One-year warranty.Please contact local distributor for accurate data

**1** 3 rows 4 colors with white color supported  
XTRA3300He supports standard 4 colors, max 9 printheads, EPSON printhead is one head two channels. LC,LM,W,V are optional.

**2** Printhead anti-crash function  
Carriage will stop in case printheads are lower than media. It helps to protect printhead from crash damage caused by improper operation or bad material quality.

**3** LED light box system  
Built-in LED light strip for previous light box performance as printing

**4** Adjustable suction platform  
Adjustable printing platform suction reduces material wrinkle to guarantee printing precision.

**5** Solenoid ink purge and flushing system  
Easy to perform, and ink-saving.

**6** Automatic media locating system  
Media locating bat helps confirming printing initial position and ensuring accuracy.

**7** Automatic height adjusting system  
Automatically detecting media thickness and adjusting printhead height function enable pointing over 45mm thick substrates.It greatly improves automation and image output quality.

**8** Automatic take-up and feed-in system  
Equipped with air shaft and motor with adjustable rotate speed, it can meet the take-up and feed-in, requirements of materials with different thickness, and avoid wrinkle issues.

**9** Automatic dual negative pressure system  
Automatic negative pressure adjustment stable and smart. Independent white ink negative pressure system prevents white ink dripping problem and improves white ink fluency.

**10** Infrared safeguard  
Optional. Infrared safeguard auto detect the impediment in the take up and feeding system,area, secure the safe production.

**11** Approved by EU and international standard system.  
Conforming to ISO9001, 2008 international standard system.

